

UPS 2000VA UL2000

UL2000 UPS-2000VA/1200W

- Input Voltage Range: 145-290V
- Output Voltage Range: 220V±10%
- With 12V9AH*2pc
- EU Output socket*4pcs
- EU Plug

Capacity	2000VA
Mode	Offline
Form	Tower
Battery	9Ah



Detailed

Model	UL2000
Capacity	2000VA
Input voltage range	145~290Vac
Output voltage range	220V±10%
Output frequency	47-54Hz(DC Mode)
Wave form	Simulated Sine Wave
Transfer time	Typical 4-6ms, maximum 10ms.
QTY & capacity of battery	2 pcs*12V9Ah
Charging period	8 hours recover to 90% capacity
Backup time	30-38 minutes□1PC+19 inch LED Monitor)
USB communication port/RJ11/RJ45	Optional
Automatic charging (offline charging)	Yes
Battery low voltage protection	Yes

Short circuit & Overload protection	Yes	
Auto restart while AC is recovering	Yes	
Silence function when the UPS on battery mode	Yes	
Euro output socket	4pcs	
Unit dimension (mm)	365*138*165	
Color box dimension (mm)	430*210*235	
Master box dimension (mm)	450*436*250	
Pcs in one master carton	2	
Gross weight (1pc, kg)	12,3	
Net weight (1pc, kg)	12	