

DMA6650U Mixer Amplifier 6 Zones

DMA6650U 650W 6 Zones Digital Mixer Amplifier with Remote Paging Station

- 70V/100V & 4-16Ω speaker output
- Rated power:650W
- Input source: 4 Mic, 4 AUX and USB/FM/Bluetooth/TF
- Support 6 remote paging microphones
- With 19" rack mount handles
- Phoenix port for Mic2-4 input ,Line2 input ,EMC input,
- Mute and Siren
- Mic 2-4 with phantom power 48V
- Individual volume control and Bass/Treble adjustment
- Priority: MUTE>EMC IN=SIREN>MIC1=CHIME=
- Remote Mic>Mic2-Mic4/AUX input/Bluetooth/FM/USB
- Protection: Overload, Clipping, Short circuit and temperature protection
- Power supply: AC220V-230V/50Hz/60Hz or DC24V

Power	650 W
-------	-------



Model		DMA6650U
Power		AC220-230V 50 / 60Hz
Input Sensitivity	MIC1	5mV ±1mv (Balanced XLR Input)
	MIC2/MIC3/MIC4	5mV ±1mv (Unbalanced Phoenix Jacks)
	AUX1	350mV±50mv (Unbalanced RCA Input)
	AUX2	350mV ±50mv (Unbalanced Phoenix Jacks)
	EMC	350mV ±50mv (Unbalanced Phoenix

		Jacks)
MIC Frequency Response		120Hz~ 12kHz (±3dB)
AUX Frequency Response		80Hz~ 15kHz (±3dB)
THD		<1%
Treble Adjustment Range		10dB±2
BASS Adjustment Range		10dB±2
Phantom Power		+48±5V
Rated Output Power		650W
Static Power Consumption	AC220-230V Power Supply	40.8W
	DC24V Power Supply	37.7W
Rated Power Consumption	AC220-230V Power Supply	800W
	DC24V Power Supply	435W
Output Voltage of Port		4-16Ω,70V,100V(fixed voltage output)
Current		4A
Protection		F8AL
Machine Dimension(D×W×H)		430×390×88mm
Package Dimension:		545×500×165mm
Net Weight		11KG