

PoE Switch FF-M41D

FF-M41D 4*1000M POE Port+1*1000M Uplinked

- One Port ≤ 30W
- Full Port ≤ 65W
- AC 100V-240V Short circuit protection
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode
- Distance: ≤ 150M
- AI Extended Mode

Port Number	4 Port
Port speed	1000mbp/s
PoE	PoE
PoE power	65 W



Detailed

Model	FF-M41D
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+3/6- and 4/5+7/8-
Whole Power	≤65W (52V 1.5A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤100m
Network Standard	IEEE 802.3u IEEE802.3u IEEE802.3x IEEE802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	20Gbps
SFP	1CH SFP 100/1000Mbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-tx:14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning

	and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature□-10°-- 55°C
Weight	0.85kg
Size	125×115×33(L*W*H)mm