

FF-W2 Point to Point

FF-W2 2 *10/100Mbps RJ45 LAN Ports

- IEEE 802.11a/n/ac, IEEE802.3, IEEE802.3u
- WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PS
- Comply with 5.8GHz IEEE802.11a/n/ac standard, the Wi-Fi data rate is up to 450Mbps
- DC 12V, input POE 24V



Detailed

CPU	Realtek RTL8881 533MHz
Standards Comply	IEEE802.11a/n/ac, IEEE802.3u, IEEE 802.3x
DDR	32Mbyte
FLASH	8Mbyte
Power Supply	DC 12V, passive POE 24V
Antenna	Internal 14dBi directional panel dual-polarization antenna (horizontal beam 60°, Vertical beam 25°)
RF Power	5.8GHz 20.0 ± 2.0dBm
Ethernet Ports	1 10/100Mbps RJ45 LAN Ports
Reset Button	1x Reset button, Restore factory default settings
Firmware upgrade	Through Web and TFTP
LED Indicator	POWER, LAN, WIFI, RSSI1, RSSI2
Data Transfer Rate	5.8GHz 450Mbps
Transmission Type	DSSS
Modulation Type	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK
RF Frequency range	5.180 GHz ~ 5.850 GHz (Channel 36~165)
Product Size	201*78*56mm

Environmental Requirement	
Working Temperature	-20~+60°C
Working Humidity	10%~95% RH □non-condensation□
Storage Temperature	-80~+90°C
Storage Humidity	10%~95% RH □non-condensation□
Lightning Protection	Common mode 1.5KV, differential mode 1KV

Daytech.Az