

PoE Switch FF-Q2444B

FF-Q2444B 24*1000M POE Port+4*1000M Uplinked+4SFP

- Compatible with IEEE802.3AF/AT
- One Port≤30W
- Full Port≤350W
- AC 100V-240V Short circuit protection
- Distance:≤150M
- AI Extended Mode
- 1U Standard rack

Product Name	24 CH Full Gigabit POE Switch(24+4+4)
Product Model	FF-Q2444B
DATA PIN	1/2+,3/6- 4/5+7/8-
Power Supply Type	Build In, 1/2+,3/6-
Max. PoE Power for single port	15.4W/30W
Connector	24*1000Mbps POE port,4*1000Mbps Uplink port,4*1000Mbps SFP
Network Medium	Cat5 (UTP) or more
Technology	
Network Standards	IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3z IEEE 802.3ab 1000BASE-T
PoE power	IEEE 802.3x Flow Control IEEE 802.3af/at Power over Ethernet 30W per port(IEEE802.3af/at).
Processing types	Wiring: Data & power provided over pairs 1/2 and 3/6 Store-and-forward Half-duplex back pressure and IEEE 802.3x full-duplex flow control
Address database Table Size	8K MAC address
Buffer memory	48Kb embedded memory per unit
Backboard Bandwidth	56Gbps Full duplex
Network Latency	Less than 20us for 64 byte frames in store-and-forward mode for 1000Mbps to 1000Mbps transmission
Power	
Input	AC 110-240 V, 50/60 Hz
PoE power consumption	30W per port(IEEE802.3af/at)
Overload current protection	Present
Mechanical	
Casing	Metal
Installation	Rack mounting
Interface	
LED Indicators	System: Power Per port: Link,PoE active
Environment specification	
Operating temperature	-10-55°C
Storage temperature	-40-70°C
Operating humidity	90% maximum relative humidity, non-condensing
Storage humidity	95% maximum relative humidity, non-condensing
Regulatory Approval	
ISO	Manufactured in ISO9001 facility
Safety	CE/CCC
Warranty	2 Years
Dimensions	440*285*55mm (L*W*H)
Weight	N.W:3.6Kg G.W:4.2Kg

Port Number	24 Port
Port speed	1000mbp/s
PoE	PoE

PoE power

30 W



Detailed

Product Model	FF-Q2444B
DATA PIN	1/2+,3/6- 4/5+7/8-
Power Supply Type	Build In, 1/2+,3/6-
Max. PoE Power for single port	15.4W/30W
Connector	24*1000Mbps POE port,4*1000Mbps Uplink port,4*1000Mbps SFP
Network Medium	Cat5 (UTP) or more
Technology	
Network Standards	IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3z IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at Power over Ethernet
PoE power	30W per port(IEEE802.3af/at). Wiring: Data & power provided over pairs 1/2 and 3/6
Processing types	Store-and-forward Half-duplex back pressure and IEEE 802.3x full-duplex flow control
Address database Table Size	8K MAC address
Buffer memory	48Kb embedded memory per unit
Backboard Bandwidth	56Gbps Full duplex
Network Latency	Less than 20us for 64 byte frames in store-and-forward mode for 1000Mbps to 1000Mbps transmission
Power	
Input	AC 110-240 V, 50/60 Hz
PoE power consumption	30W per port(IEEE802.3af/at)
Overload current protection	Present
Mechanical	
Casing	Metal
Installation	Rack mounting
Interface	
LED Indicators	System: Power Per port: Link,PoE active
Environment specification	

Operating temperature	-10-55°C
Storage temperature	-40-70°C
Operating humidity	90% maximum relative humidity, non-condensing
Storage humidity	95% maximum relative humidity, non-condensing
Regulatory Approval	
ISO	Manufactured in ISO9001 facility
Safety	CE/CCC
Warranty	2 Years
Dimensions	440*285*55mm (L*W*H)
Weight	N.W:3.6Kg G.W:4.2Kg

Daytech.Az