

Amplifier DS-6180A

Amplifier DS-6180A 6 Zone 180W

USB interface, Bluetooth, MP3, SD card playback, LED display

Two mics, one with silence

Microphone with reverberation adjustment to control delay, frequency and depth

Power	180 W
-------	-------



Detailed

Model	DS-6180A
Rated output power	180W
Ambient Humidity	20% ~ 80% relative humidity, no condensation
Transmission Rate	10Mbps/100Mbps
Audio Format	MP3/MP2
Audio Mode	16-32 bit stereo CD quality
Sampling Rate	8K ~ 256K
Bit Rate	8K ~ 512Kbps
EMC Input Sensitivity	775mV
AUX Input Sensitivity	350mV
MIC Input Sensitivity	10mV
Standby Power Consumption	< 0.2W
Harmonic Distortion	THD≤0.1%

Signal to noise ratio	≥85dB
Frequency response	50Hz-18KHz ≤±3dB
Output mode	6 LINE Output
THD (Total harmonic distortion)	0.1%(1KHZ 0dB)
SNR (Signal to noise Ratio)	Microphone - 66dB LINE - 102dB
Input sensitivity	Microphone - -50db/600Ω LINE - -10dB/10KΩ
Power Supply	AC220V/50HZ
Dimension	484*410*88mm