

Amplifier DS-6240A

Amplifier DS-6240A 6 Zone 240W

USB interface, Bluetooth, MP3, SD card playback, LED display

Two mics, one with silence  
Microphone with reverberation adjustment to control delay, frequency and depth

|       |       |
|-------|-------|
| Power | 240 W |
|-------|-------|



|                           |                                              |
|---------------------------|----------------------------------------------|
| Model                     | DS-6240A                                     |
| Rated output power        | 240W                                         |
| Ambient Humidity          | 20% ~ 80% relative humidity, no condensation |
| Transmission Rate         | 10Mbps/100Mbps                               |
| Audio Format              | MP3/MP2                                      |
| Audio Mode                | 16-32 bit stereo CD quality                  |
| Sampling Rate             | 8K ~ 256K                                    |
| Bit Rate                  | 8K ~ 512Kbps                                 |
| EMC Input Sensitivity     | 775mV                                        |
| AUX Input Sensitivity     | 350mV                                        |
| MIC Input Sensitivity     | 10mV                                         |
| Standby Power Consumption | < 0.2W                                       |
| Harmonic Distortion       | THD≤0.1%                                     |
|                           |                                              |

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| Signal to noise ratio           | ≥85dB                                        |
| Frequency response              | 50Hz-18KHz ≤±3dB                             |
| Output mode                     | 6 LINE Output                                |
| THD (Total harmonic distortion) | 0.1%(1KHZ 0dB)                               |
| SNR (Signal to noise Ratio)     | Microphone - 66dB<br>LINE - 102dB            |
| Input sensitivity               | Microphone - -50db/600Ω<br>LINE - -10dB/10KΩ |
| Power Supply                    | AC220V/50HZ                                  |