

UPS 3KVA UNRB1103KS

3KVA/3KW Rask type online UPS standard backup, RS232/USB/EPO/Smart socket, 6pcs 12V 9AH batteries, EU input plug and output socket, 220V/50HZ.

Capacity	3KVA
Mode	Online
Form	Rackmount
Battery	9Ah



Detailed

Model	UNRB1103KS	
Capacity	3kVA/3kW	
Input		
Nominal Voltage	208/ 220/230/240Vac, L+N+PE	
Voltage Range	110~300Vac	
Frequency Range	40-70Hz	
Power Factor	≥0.99	
THDi	≤4% (linear load); ≤5% (non-linear load)	
Output		
Nominal Voltage	208/220/230/240Vac ,L+N+PE	
Voltage Regulation	±1%	
Frequency	50/60Hz ± 0.1%	
THDu	≤2% (linear load); ≤5% (non-linear load)	
Hamonic Distrotion		
Transfer Time	Zero	
Waveform	Pure sine wave	
Crest Factor	3:1	
Overload Capacity	102%~110% load, 30min;110%~130% load, 10min;	
(Line Mode)	130%~150% load, 30s; >150% load, 200ms	
Overload Capacity	102%~110% load, 1min;110%~130% load, 10s;	
(Battery Mode)	130%~150% load, 3s;>150% load, 200ms	
Efficiency		
Line Mode	95.5%	
Battery Mode	91.5%	

ECO Mode		98%
Battery		
Battery Voltage	72Vdc	
Battery Number	9Ah*6pcs	
Charge Current	1A	
Communication		
Interface		RS232 / USB/ Snmp Card(optional) /Dry contact card(optional)
Environment		
Operation		0~40℃
Temperature		
Humidity		0~95%(non-condensing)
Noise		≤50dB@1meter away
Altitude		Up to 1000m without derating
Physical		
Dimensions	440*568*86	
(W*D*H)mm		
Weight (kg)	22.5	