

UPS 10KVA UN1110KS

10KVA/10KW tower type online UPS standard backup, with RS232/USB/EPO/Intelligent slot,192VDC,16pcs*7AH

Capacity	10KVA
Mode	Online
Form	Tower
Battery	9Ah

**Detailed**

Model	UN1110KS
Capacity	10KVA/10kW
Input	
Nominal Voltage	208/ 220/230/240Vac, L+N+PE
Voltage Range	110~300Vac
Frequency Range	40-70Hz
Power Factor	≥0.99
THDi	≤5%(linear load); ≤8%(non-linear load)
Output	
Nominal Voltage	208/220/230/240Vac, L+N+PE
Voltage Regulation	±1%
Frequency	50/60Hz±0.1%
THDu	≤2% (linear load); ≤5% (non-linear Load)
Transfer Time	Zero
Waveform	Pure Sine Wave
Crest Ratio	3:1
Overload Capacity (Line Mode)	102%~105% load, 30min; 105%~125% load, 10min; 125%~150% load, 30s; >150% load, 500ms
Overload Capacity (Battery Mode)	102%~105% load, 10min; 105%~125% load, 1min; 125%~150% load, 10s; >150% load, 500ms
Battery	
Battery Type	Sealed lead acid Maintenance Free
Battery Voltage	192Vdc / 240Vdc
Battery Number	9Ah*16/20pcs
Charging Current	1A
Efficiency	

Line Mode		95%
Battery Mode		94.5%
ECO Mode		98%
Communication		
Interface	RS232 / USB/ Snmp Card (optional) /Dry contact card (optional)	
Environment		
Operation Temperature	0~40°C	
Humidity	0~95%(non-condensing)	
Noise	≤50dB@1meter away	
Altitude	Up to 1000m without derating	
Physical		
Dimensions (W*D*H) mm	250*523*602	
Weight (kg)	75/84.2	

Daytech.Az