

## UPS 10KVA UN1110KS

10KVA/10KW tower type online UPS standard backup, with RS232/USB/EPO/Intelligent slot,192VDC,16pcs\*7AH

Capacity	10KVA
Mode	Online
Form	Tower
Battery	9Ah



### Detailed

<b>Model</b>	<b>UN1110KS</b>	
Capacity	10kVA/10kW	
<b>Input</b>		
Nominal Voltage	208/ 220/230/240Vac, L+N+PE	
Voltage Range	110~300Vac	
Frequency Range	40-70Hz	
Power Factor	≥0.99	
THDi	≤5%(linear load); ≤8%(non-linear load)	
<b>Output</b>		
Nominal Voltage	208/220/230/240Vac, L+N+PE	
Voltage Regulation	±1%	
Frequency	50/60Hz±0.1%	
THDu	≤2% (linear load); ≤5% (non-linear Load)	
Transfer Time	Zero	
Waveform	Pure Sine Wave	
Crest Ratio	3:1	
Overload Capacity (Line Mode)	102%~105% load, 30min; 105%~125% load, 10min; 125%~150% load, 30s; >150% load, 500ms	
Overload Capacity (Battery Mode)	102%~105% load, 10min; 105%~125% load, 1min; 125%~150% load,10s; >150% load, 500ms	
<b>Battery</b>		
Battery Type	Sealed lead acid Maintenance Free	
Battery Voltage	192Vdc / 240Vdc	
Battery Number	9Ah*16/20pcs	
Charging Current	1A	
<b>Efficiency</b>		

Line Mode		95%
Battery Mode		94.5%
ECO Mode		98%
<b>Communication</b>		
Interface		RS232 / USB/ Snmp Card (optional) /Dry contact card (optio
<b>Environment</b>		
Operation Temperature		0~40°C
Humidity		0~95%(non-condensing)
Noise		≤50dB@1meter away
Altitude		Up to 1000m without derating
<b>Physical</b>		
Dimensions (W*D*H) mm	250*523*602	
Weight (kg)	75/84.2	