

UPS 6KVA UNR1106KL

6KVA/6KW online Rack UPS long backup, with RS232/USB/EPO/Intelligent slot,External Battery,192VDC,220V/50HZ,

Capacity	6KVA
Mode	Online
Form	Rackmount
Battery	External



Detailed

Model	UNR1106KL	
Capacity	6kVA/6kW	
Input		
Nominal Voltage		208/ 220/230/240Vac, L+N+PE
Voltage Range		110~300Vac
Frequency Range		40-70Hz
Power Factor		≥0.99
THDi		≤5%(linear load); ≤8%(non-linear load)
Output		
Nominal Voltage		208/220/230/240Vac, L+N+PE
Voltage Regulation		±1%
Frequency		50/60Hz±0.1%
THDu		≤2% (linear load); ≤5% (non-linear Load)
Transfer Time		Zero
Crest Ratio		3:1
Overload Capacity (Line Mode)		102%~105% load, 30min; 105%~125% load, 10min; 125%~150% load, 30s; >150% load, 500ms
Overload Capacity (Battery Mode)		102%~105% load, 10min; 105%~125% load, 1min; 125%~150% load,10s; >150% load, 500ms
Battery		
Battery Voltage		192Vdc / 240Vdc
Battery Number	External	
Charging Current	1-12A settable	
Efficiency		
Line Mode		95%
Battery Mode		94.5%

ECO Mode		98%
Communication		
Interface		RS232 / USB/ Snmp Card(optional) /Dry contact card (option)
Environment		
Operation Temperature		0~40℃
Humidity		0~95%(non-condensing)
Noise		≤50dB@1meter away
Altitude		Up to 1000m without derating
Physical		
Dimensions (W*D*H) mm	440x487x86	
Weight (kg)	15	