

UPS 3000VA UNB3000

UPS UNB3000

- Rated Voltage: 110/120Vac
- Voltage Range: 85-145Vac
- Frequency Range: 45-65Hz
- Waveform: PWM (Battery mode)
- Transfer Time: Typical 2-6ms, 10ms max

Capacity	3000VA
Rejim	Line-interaktiv
Battery	9Ah



Ətraflı

Model	UNB3000
Capacity	3000VA/1800W
Input	
Rated Voltage	110/120Vac, L+N+PE
Voltage Range	85-145Vac
Frequency Range	45-65Hz
Output	

Rated Voltage	110/120Vac, L+N+PE
Voltage Range	102-132Vac
Frequency	60±0.5Hz or 50±0.5Hz (Battery mode)
Waveform	PWM (Battery mode)
Transfer Time	Typical 2-6ms, 10ms max.
Battery	
Battery Type	Valve-regulated lead-acid maintenance-free battery
BatteryNumber	9Ah*4
Charging Time	4 hours
Protection	
Full Protection	Low voltage & overload & short circuit protection
Indicator	
LCD or LED	Optional
Interface	
USB/RJ45 or RS232/RJ45 or None	Optional, support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC
Environment	
Operation Temperature	0-40℃
Humidity	20-90% (Non-condensing)
Noise Level	≤40dB(1m away)
Altitude	Up to 1000m without derating
Physical	
Dimensions (W*D*H)mm	145*412*210
Weight (kg)	20

