

UPS 1000VA UNA1000

UPS UNA1000

- Rated Voltage: 110/120Vac or 220/230/240Vac
- Voltage Range: 85-145Vac or 145-290Vac
- Operation Temperature: 0-40°C
- Humidity: 20-90% (Non-condensing)

Capacity	1000VA
Rejim	Line-interaktiv
Battery	7Ah



Ətraflı

Model	UNA1000
Capacity	1000VA/600W
Input	
Rated Voltage	110/120Vac or 220/230/240Vac
Voltage Range	85-145Vac or 145-290Vac
Frequency Range	45-65Hz
Output	
Rated Voltage	110/120Vac or 220/230/240Vac, L+N+PE
Voltage Range	102-132Vac or 200-255Vac
Frequency	60±0.5Hz or 50±0.5Hz (Battery mode)
Waveform	PWM (Battery mode)
Transfer Time	Typical 2-6ms, 10ms max.
Battery	
Battery Type	Valve-regulated lead-acid maintenance-free battery
BatteryNumber	7Ah*2
Charging Time	4-6 hours recover to 90% capacity
Protection	
Full Protection	Low voltage & overload & short circuit protection
Indicator	
LCD or LED	Optional
Interface	

USB/RJ45 or None	Optional, support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC
Environment	
Operation Temperature	0-40°C
Humidity	20-90% (Non-condensing)
Noise Level	≤40dB(1m away)
Altitude	Up to 1000m without derating
Physical	
Dimensions (W*D*H)mm	330*122*192
Weight (kg)	8.5