

Audio Conference DMX08

DMX08 Conference

3 equalization adjustments per channel MUTE

60MM smooth fader attenuator

1 set of return, 1 set of RAC output

48V phantom power supply

16 kinds of DSP digital effector. USB , Bluetooth USB recording

LED display , Ten-segment three-color level light

1 set of stereo bus output 2 sets of AUX bus output



Ətraflı

| Model                  | DMX08            |  |
|------------------------|------------------|--|
| MAX. Output Level      | 18dB             |  |
| S/N                    | ≥83dB            |  |
| THD                    | ≤0.02% @0dB 1KHz |  |
| Frequency Response     | 20Hz~20KHz±0.5dB |  |
| Channel Crosstalk      | □-75dB @ 1KHz    |  |
| Input Impedance MIC    | 600Ω             |  |
| LINE                   | 10KΩ             |  |
| Output Impedance       | 100Ω             |  |
| MIC IN                 | -60dB            |  |
| LINE IN                | -40dB            |  |
| Stereo Input Impedance | 10KΩ             |  |
| Channel Gain           | -30dB            |  |
| 3-band EQ              | ±15dB            |  |

|                    |                  |
|--------------------|------------------|
| HI                 | 12KHz 15dB ±3dB  |
| MID                | 2.5KHz 15dB ±3dB |
| LOW                | 80Hz 15dB ±3dB   |
| Output Power       | 30W              |
| Power Supply       | 100V-240V/50Hz   |
| Package Dimensions | 440×440×165mm    |
| Product Dimensions | 385×367×100mm    |
| Gross Weight       | 5kg              |
| Net Weight         | 4kg              |