

DX1000

This professional power amplifier features a dual-channel stereo design and a sleek new appearance. It offers a range of high-power amplifiers to meet a variety of needs for different occasions. Additionally, it comes with multiple protection modes, such as short-circuit protection, DC protection, and power on/off protection, ensuring safe and reliable operation.

- 2 Channels professional stereo power amplifier
- Multiple power range
- Each channel with individual volume control
- With XLR and a 6.35mm phone jack for audio input
- Each channel with an LED indicator for the working status
- With protection of short-circuit, DC current, high temperature, etc
- With protection of power shock, avoid damage to the electricity grid and audio equipment.

Power	150 W
-------	-------



Ətraflı

Model	DX1000
Rated Output / Channel, 8Ω	150W
Rated Output / Channel, 4Ω	250W
Rated Output / Bridge, 8Ω	500W
S/N Ratio	90dB
Damping Coefficient/8Ω, 1kHz	200:1

Input Common Mode Rejection	>90dB
Frequency Response	20Hz-20kHz (±3dB)
Harmonic Distortion Coefficient 4Ω/1kHz	< 0.3% (Under normal working conditions)
Channel Impedance	4-16Ω
Channel Crosstalk	<-70dB
Display	“Power”, “Clip”, “Signal”, “DC” and “TEMP” LEDs
Power Consumption	700W
Operating Power	AC220V/50Hz
Protection	Power on/off, DC output, load short circuit.
Machine Dimensions (mm)	(L×W×H) 483×396×88
Package Dimensions (mm)	(L×W×H) 540×460×165
Gross Weight	8.5kg
Net Weight	6.5kg