

Switch CAM-P1024UG

This CAM-P1024UG switch provides a network point for power supply and data transmission. All the 24 PoE ports can be connected with 10/100Mps quickly, and the uplink port is 1.25Gbps fiber interface, among which 1-24 ports can provide standard IEEE802.3af/at power supply. Due to the advanced self-sensing algorithm supply power for IEEE802.3af/at terminal unit only, there is no need to worry about damaging proprietary PoE or non-PoE standard equipment. In addition, it will stop power supply when PoE devices are not connected. In short, The CAM-P1024UG features simple and reliable design, automatic identification of PoE requirements, duplex and high-speed. The devices far away power socket are very suitable for hanging on the wall or ceiling. PoE eliminates the need for connecting these devices to the power socket. So it makes it more flexible for those difficult to connect with AC power socket, and cut down the installation cost. It is an ideal choice for those who want to deploy a small commercial network.

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	250 W
Type	Managed



Detailed

Model	CAM-P1024UG
Maximum Power	Single-port, 15.4 W/30 W
POE Port	24*10 Mbps
Port	2*10/100/1000Mbps
Bandwidth	8.8 GB
Sequence of power supply lines	12+ 36-
Built-in power supply, additional	250 W/400 W

Mode support	CCTV
Optional Mounting Eyes	19" 1U/Rack-Mount
PoE Standard	IEEE802.3af and IEEE802.3at

Daytech.Az