

## Access Control ASA3213GL-MW

FACT Time Attendance Terminal

- > 4.3-inch LCD touch screen; resolution 480 × 272
- > With 2MP wide-angle dual lens, white LED illuminator, IR light
- > Support face, card and password attendance
- > Support 500 users, 500 face images, 500 cards, 150,000 records and work without network
- > Face verification accuracy 99.5%; face comparison speed 0.3 s per person; low false recognition rate; support liveness detection



## Ətraflı

System	
Main Processor	Embedded Processor

Network Protocol	IPv4, RTSP, RTP, TCP, UDP, P2P
OSDP Protocol	Support
Interoperability	CGI
SDK	Support
Basic	
Display Screen	4.3-inch TFT screen
Screen Type	Capacitive screen
Resolution	480 × 272
Camera	2MP CMOS high definition camera
Voice Prompt	Yes
Casing	PC+ABS
Function	
Card Type	IC card
Network Update	Yes
Peripheral Card Reader	1 RS-485
Real-Time Surveillance	Yes
Multiple Authentication	Yes
Take Face Images after Swiping Cards	Yes
Auto-Registration	Yes
Attendance	
Attendance Record Export	USB flash drive export
Attendance Mode	Fixed attendance; free attendance
Attendance Statistics	Statistics by personnel, month, anomaly
Department Setting	20 departments

Shift Setting	24 shifts
<b>Capacity</b>	
User Capacity	500
Face Capacity	500
Card Capacity	500
Password Capacity	500
Record Capacity	150,000
<b>Port</b>	
RS-485	1
USB	1 USB2.0 port
Network	1 RJ-45, 10 Mbps/100 Mbps self-adaption
Alarm Input	1
Alarm Linkage	Yes
Exit Button	1
Door Status Detection	1
Lock Control	1
<b>Alarm</b>	
Tamper	Yes
<b>General</b>	
Power Adapter	Included
Power Supply Mode	DC 12V 1.5A
Power Consumption	≤ 18W
Product Dimensions	116 mm × 107 mm × 22 mm (4.57" × 4.21" × 0.87") (H×W×D)
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	5%RH-95%RH (non-condensing)

Operating Environment	Indoor
Installation Method	Surface mount; desktop mount
Certification	CE/FC