

## VTH2421FW-P

Monitor for doorphone Dahua

7-inch TFT Screen;

1024 x 600 Resolution;

Simplified Connection and Setup to Compatible Outdoor Stations;

Integrated Micro SD Card Slot, maximum 32 GB;

Perform Call Session Recordings and Take Snapshots of Live Video(requires SD card);

Setup and Activate up to Six (6) Alarm Inputs.

Connection type	Analog
Device	Monitor
Memory	Memory
Material	Plastic



## Detailed

<b>Model</b>	<b>VTH2421FW-P</b>
<b>System</b>	
Main processor	High-performance embedded processor
operating system	Embedded LINUX OS
Screen type	Capacitive screen

<b>Display</b>	
Screen	7-inch TFT screen
Permission	1024×600
<b>Video</b>	
Video compression	H.264
<b>Audio</b>	
Audio compression	G.711A/G.711U/PCM
Audio input	1 channel omnidirectional microphone
Audio output	Built-in speaker 1.5W
Audio mode	Support two-way communication
Sound enhancement	Support echo cancellation/DNR
Audio bitrate	16 kbps
<b>Anxiety</b>	
Alarm input	6 channels (number of switches)
Alarm exit	Channel 1
SOS alarm	Supports
<b>Net</b>	
Net	1 RJ-45
<b>Basic information</b>	
Communication mode	Full digital
Sending video and text messages	Supports
DND mode	Supports to set DND period
Number of substations	9
Storage	Support Micro SD card, maximum memory 32GB, standard memory 8GB

<b>Environment</b>	
Operating temperature	-10°C to +55°C (+14°F to +131°F)
Working humidity	10% - 95% relative humidity
<b>Electrical properties</b>	
Power supply	Standard PoE DC 12V 1A
Power consumption	Standby ≤4W; Working ≤6W
Diet	PoE
<b>General information</b>	
Frame	PC+ABS
Fastening	Wall mounted
Dimensions	119.6 mm × 221.5 mm × 21.5 mm (4.71" × 8.72" × 0.85")
Weight	0.35 kg (0.77 lb)