

## Camera VTO2311R-WP

Dahua Doorbell Camera

- Ultra-slim design
- PC and ABS material make it ideal for indoor and outdoor use
- 1/2.8" 2-MP HD CMOS camera
- Video call and unlock via app
- IR illumination and auto WDR
- Wi-Fi connectivity
- IP65 rating
- H.264 and H.265
- Unlock via interface card
- PoE power supply

Type	Analog
Megapixel	2 MP
Objective	Varifocal
Focus	2.8 mm
Lighting	IR
Protection	IP65
Material	Plastic



## Detailed

<b>System</b>	
Main Processor	Embedded Processor
Button Type	Mechanical
Interoperability	ONVIF; CGI
Network Protocol	RTSP; DNS; P2P; UPnP; RTP; RTMP; SIP; SSH; HTTP/HTTPS; ONVIF
<b>Basic</b>	

Camera	1/2.8" CMOS 2-MP HD camera
Field of View	H: 110°; V: 62°; D: 133°
WDR	120 dB
Noise Reduction	3D NR; 2D NR
Video Compression	H.264; H.265
Video Resolution	Main stream: 720p, WVGA, D1, and CIF Sub stream: 1080p, WVGA, D1, QVGA, and CIF
Video Frame Rate	PAL: 25 fps NTSC: 30 fps
Video Bit Rate	768 kbps-8 Mbps
Light Compensation	Auto IR
Day/Night	Auto (ICR)/Color/B/W; Color/B/W
Audio Compression	G.711a; G.711u; PCM
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression/digital noise reduction; Echo suppression; Digital noise reduction
Audio Bit Rate	16 kHz, 16 bit
<b>Function</b>	
Communication Mode	Full digital
Unlock Mode	Card; app; indoor monitor
Card Type	IC card
Auto Snapshot	Yes (SD card is inserted in the indoor monitor or door station)
Leave Videos	Yes (SD card inserted in VTH/VTO is needed)
Web Configuration	Yes
Wi-Fi	Yes

Wireless Standard	IEEE 802.11b; IEEE 802.11g; IEEE 802.11n
Wireless Frequency Range	2.4 GHz
Storage	Micro SD card (max. 256 GB)
<b>Performance</b>	
Card Reading Distance	0 cm-3 cm (0"-1.18")
Issue Card Locally	Yes
Casing	PC+ABS
<b>Capacity</b>	
Card Capacity	3000
<b>Port</b>	
Exit Button	1
Door Status Detection	1
Lock Control	1
Network Port	1 × RJ-45 10/100 Mbps Ethernet port
<b>Alarm</b>	
Tamper Alarm	Yes
<b>General</b>	
Appearance color	Light grey
Power Supply	12-33 VDC, 1 A ; Standard PoE
Power Adapter	Optional
Installation	Surface Mount
Certifications	CE; FCC
Accessory	Included: Alarm power ribbon cable, rain cover
Product Dimensions	160 mm × 50 mm × 30 mm (6.30" × 1.97" × 1.18")

Protection	IP65
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	10%-90% (RH), non-condensing
Operating Altitude	0 m-3,000 m (0 ft-9,842.51 ft)
Power Consumption	≤ 3.5 W (standby), ≤ 6 W (working)
Gross Weight	0.4 kg (0.88 lb)
Net Weight	0.18 kg (0.40 lb)