

DS-2CE76D3T-ITMF

DS-2CE76D3T-ITMF 2,8MM 2MP HD TVI AHD CVI CVBS KAMERA HIKVISION

- 2 MP turret camera
- Strong night performance, capturing images in ultra-low light down to 0.005 lux
- Clear imaging even against strong back lighting due to 120 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- EXIR 2.0: advanced infrared technology with 30 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (TVI/AHD/CVI/CVBS)

|                       |        |
|-----------------------|--------|
| Növ                   | Analoq |
| Megapixel             | 2 MP   |
| Obyektiv              | Sabit  |
| Fokus                 | 2.8    |
| İşıqlandırma          | İR     |
| İşıqlandırma məsafəsi | 30 m   |
| Qoruma                | IP67   |
| Material              | Metal  |



Ətraflı

| Camera            |                                                       |
|-------------------|-------------------------------------------------------|
| Image Sensor      | 2.0 megapixel progressive scanCMOS                    |
| Max. Resolution   | 1920 (H) × 1080 (V)                                   |
| Min. Illumination | 0.005 Lux@(F2.0, AGC ON), 0 Lux withIR                |
| Shutter Time      | PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s  |
| Day □ Night       | IR Cut Filter                                         |
| Angle Adjustment  | Pan: 0° to 360°,Tilt: 0° to 75°, Rotation: 0° to 360° |

|                          |                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------|
| Signal System            | PAL/NTSC                                                                                                         |
| <b>Lens</b>              |                                                                                                                  |
| Lens Type                | 2.8 mm, 3.6 mm, 6 mm                                                                                             |
| Focal Length∅ FOV        | 106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)                                                                          |
| Lens Mount               | M12                                                                                                              |
| <b>Illuminator</b>       |                                                                                                                  |
| Supplement LightType     | IR                                                                                                               |
| Supplement LightRange    | Up to 30 m                                                                                                       |
| Smart Supplement Light   | Yes                                                                                                              |
| <b>Image</b>             |                                                                                                                  |
| Image Parameters Switch  | STD/HIGH-SAT                                                                                                     |
| Image Settings           | Brightness,Mirror,Sharpness,AGC                                                                                  |
| Frame Rate               | PAL: 1080p@25fps<br>NTSC: 1080p@30fps                                                                            |
| Day/Night Mode           | Auto/Color/BW (Black and White)                                                                                  |
| Wide Dynamic Range (WDR) | ≥120 dB                                                                                                          |
| Image Enhancement        | WDR,BLC,HLC                                                                                                      |
| Noise Reduction          | 3D DNR                                                                                                           |
| <b>Interface</b>         |                                                                                                                  |
| Video Output             | Switchable TVI/AHD/CVI/CVBS,1 HD analog output                                                                   |
| <b>General</b>           |                                                                                                                  |
| Power                    | 12 VDC ±25%, max. 4.6 W<br><br>*You are recommended to use one power adapter to supply the power for one camera. |
| Material                 | Metal                                                                                                            |
| Dimension                | 89.47 mm × 68.2mm (3.52" × 2.68")                                                                                |

|                     |                                                                             |
|---------------------|-----------------------------------------------------------------------------|
| Weight              | Approx. 240 g (0.53lb.)                                                     |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less(non-condensation) |
| Language            | English                                                                     |
| <b>Approval</b>     |                                                                             |
| Protection          | IP67                                                                        |