

Kamera DS-2CE16D0T-LPFS

DS-2CE16D0T-LPFS 2.8mm 2mp Smart IR 25m LED 20m HD MINI BULLET KAMERA HIKVISION

- High quality imaging with 2 MP, 1920×1080 resolution
- 2.8 mm fixed focal lens
- Up to 25 m IR distance for bright night imaging
- Up to 20 m white light distance for bright night imaging
- One port for four signals (TVI/AHD/CVI/CVBS)
- High quality audio with audio over coaxial cable, built-in mic
- Water and dust resistant (IP67)
- Smart-Hybrid light, optimize your security with flexible lighting options

Növ	Analoq
Megapixel	2 MP
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	25 m
Mikrofon	Mic
Qoruma	IP67
Material	Plastik



Ətraflı

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 sto 1/50, 000 s; NTSC:1/30 s to 1/50, 000s
Day Night	ICR

Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm fixed focal lens
Focal Length□ FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal F OV: 118°
Lens Mount	M12
Illuminator	
Supplement Light Type	White Light,IR
Supplement LightRange	IR : Up to 25 m White Light : Up to 20 m
Image	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P @ 30 fps, 1080P @ 25 fps CVI: 1080P @ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color/BW (Blackand White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
Built-in Microphone	Yes
General	
Material	Plastic

Dimension	138.8 mm × 60.9 mm × 57.9mm (5.47" × 2.4 "× 2.3")
Weight	Approx. 155 g(0.34 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera.
Consumption	Max. 3.3 W
Approval	
Protection	IP67