

DS-2CE18D0T-LFS

DS-2CE18D0T-LFS 2.8mm 2mp IR 60m LED 60m built-in mic Bullet Camera Hikvision

- High quality imaging with 2 MP, 1920 × 1080 resolution
- 2.8 mm, 3.6 mm and 6 mm fixed focal lenses
- Up to 60 m IR distance for bright night imaging
- Up to 60 m white light distance for bright night imaging
- High quality audio with audio over coaxial cable, built-in mic
- One port for four signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)
- Smart-Hybrid light, optimize your security with flexible lighting options

Type	Analog
Megapixel	2 MP
Objective	Motionless
Focus	2.8 mm
Lighting	IR
Lighting distance	60 m
Protection	IP67
Material	Metal



Detailed

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080(V)
Min. Illumination	0.01 Lux @ (F2.0, AGCON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Day □ Night	ICR

Angle Adjustment	Pan: 0 to 360°, Tilt:0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	Fixed focallens, 2.8 mm, 3.6 mm and 6 mm optional
Focal Length □ FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°,diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92° 6 mm, horizontal FOV:49.2°, vertical FOV:28.3 °, diagonal FOV: 56.1°
Lens Mount	M12
Illuminator	
Supplement LightType	White Light,IR
Supplement LightRange	IR : Up to 60 m White Light: Up to 60 m
Image	
Image Settings	Anti-Banding, Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P@ 30 fps, 1080P@ 25 fps CVI: 1080P@ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range(WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	

Power	12 VDC \pm 25%, max.9.8 W,*Youare recommended to use onepower adapter to supply the power for one camera.
Material	Front cover: Metal Main body:Plastic
Dimension	192.6 mm \times 178.3 mm \times 71 mm (7.58" \times 7.02" \times 2.8")
Weight	Approx. 738 g (1.63 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less(no n-condensation)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67