

DS-2CE19D3T-IT3ZF

DS-2CE19D3T-IT3ZF 2.7-13.5mm 2mp IR 70m VF Bullet HD TVI CAMERA HIKVISION

- 2 MP bullet camera
- Strong night performance, capturing images in ultra-low light down to 0.005 lux
- Clear imaging even against strong back lighting due to 120 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- Lens focuses automatically when zooming in or out
- EXIR 2.0: advanced infrared technology with 70 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals TVI/AHD/CVI/CVBS)

Type	Analog
Megapixel	2 MP
Objective	Motorized
Focus	2.7-13.5 mm
Lighting	IR
Lighting distance	70 m
Protection	IP67
Material	Metal



Detailed

Camera	
Matrix	2 MP Progressive Scan CMOS
Number of effective pixels	1920×1080
Sensitivity	0.005 Lux @ (F1.2, AGC on), 0 Lux with IR
Electronic shutter speed	PAL: 1/25 - 1/50,000 s NTSC: 1/30 - 1/50,000 s
Lens	From 2.7 to 13.5 mm
Lens mount	F14
Horizontal viewing angle	102 to 31°

Adjusting the viewing angle	Rotation: 0° - 360°; Tilt: 0° - 180°; Rotation: 0° - 360°
Synchronization	Internal

OSD Menu	
A.G.C.	High/Medium/Low
Day/night switching	Auto/Color/B&W
Picture Mode	STD/HIGH-SAT
WDR	There is
BLC	There is
Language	English
Peculiarities	3D DNR, Brightness, Sharpness, Mirroring, Smart IR

Interfaces	
Video output	1 analog HD video output
Switch button	TVI/AHD/CVI/CVBS

Basics	
Nutrition	DC 12V ±25%
Connection	Coaxial cable, HIKVISION-C protocol (TVI output)
Power consumption	7.7 W max
Working conditions	-40 °C...+60 °C, humidity 90% or less (non-condensing)
Protection	IP67
IR illumination range	Up to 70 m
Housing material	Metal
Dimensions	84.5 × 92 × 255.1 mm

Weight	Approximately 648 g
--------	---------------------

Daytech.Az