

DS-2CD2T47G2-LSU/SL

DS-2CD2T47G2-LSU/SL 4mm 4mp LED 60m ColorVu AcuSense Strobe Light and Audible Warning IP Big Bullet Camera Hikvision

- High quality imaging with 4 MP resolution
- Efficient H.265+ compression technology
- Clear imaging against strong backlight due to 130 dB WDR technology
- Focus on human and vehicle targets classification based on deep learning
- 24/7 colorful imaging
- Active strobe light and audio alarm to warn intruders off
- Provide real-time security via built-in two-way audio
- Audio and alarm interface available
- Water and dust resistant (IP67)

Type	IP
Megapixel	4 MP
Objective	Motionless
Focus	2.8 mm
Lighting	LED
Lighting distance	60 m
Microphone	Mic
Protection	IP67
Material	Metal



Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Min. Illumination	Color: 0.0005 Lux @ (F1.0,AGC ON), 0 Lux withwhite light
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Wide Dynamic Range	130 dB

Angle Adjustment	Pan: 0° to 360°, tilt:0° to 90°,rotate: 0° to 360°
Lens	
Focal Length& FOV	2.8 mm, horizontal FOV111.9°, vertical FOV 60.5°, diagonal FOV 133.6° 4 mm, horizontal FOV 95.2°, vertical FOV 50.6°, diagonal F OV 114.7° 6 mm, horizontal FOV 58.4°, vertical FOV 31°, diagonal FOV 68.7°
Lens Mount	M16
Aperture	F1.0
Depth of Field	2.8 mm: 3.1 m to ∞ 4 mm: 5.4 m to ∞ 6 mm: 12.1 m to ∞
DORI	
DORI	2.8 mm,D: 58.2 m, O: 23.1m, R: 11.6 m, l: 5.8 m 4 mm, D: 77 m, O: 30.5m, R: 15.4 m, l: 7.7 m 6 mm, D: 115.6m, O: 45.9m, R: 23.1 m, l: 11.6 m
Illuminator	
Smart Supplement Light	Yes
White Light Range	Up to 60 m
Visual Alarm	Yes
Video	
Max. Resolution	2688 × 1520
Main Stream	50 Hz: 25 fps (2688× 1520, 1920× 1080, 1280× 720) 60 Hz: 30 fps (2688 × 1520, 1920× 1080, 1280× 720)
Sub-Stream	50 Hz: 25 fps (1280× 720, 640× 480, 640 × 360) 60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)
Third Stream	50 Hz: 10 fps (1920× 1080, 1280× 720, 640× 480, 640 × 360) 60 Hz: 10 fps (1920 × 1080, 1280× 720, 640× 480, 640 × 360)

	*Third streamis supported undercertain settings.
Video Compression	Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264 *Third streamis supported undercertain settings.
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
H.264+	Main stream supports
H.265+	Main streamsupports
Bit Rate Control	CBR/VBR