

Kamera DS-2CE56D0T-IRM

DS-2CE56D0T-IRM 3,6mm 2mp IR 20m HD TVI TURRET METAL KAMERA HIKVISION

- 2 MP turret camera
- Smart IR: up to 25 m IR distance
- Water and dust resistant (IP67)

Növ	Analoq
Megapixel	2 MP
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	İR
İşıqlandırma məsafəsi	20 m
Qoruma	IP67
Material	Metal



Ətraflı

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01Lux @ (F2.0, AGC ON),0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30s to 1/50,000 s
Day □ Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	3.6 mm Fixed lens

Focal Length □ FOV	3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8°
Lens Mount	M12
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, SmartIR
Frame Rate	TVI: 1080P@30fps, 1080P@25fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC, HLC
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	1 HD analog output
General	
Material	Metal
Dimension	89.47 mm × 67.6mm (3.52" × 2.70")
Weight	Approx. 250 g (0.55lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25%
Consumption	Max. 3 W
IR Range	Up to 25 m

Approval	
Protection	IP67

Daytech.Az