

Camera DS-2CE56D0T-IT3E

DS-2CE56D0T-IT3E 2.8mm 2mp IR 40m Dome HD CAMERA HIKVISION

- 2 MP PoC dome camera
- EXIR 2.0: Advanced infrared technology with 40m IR range
- Water and dust resistant (IP67)
- Transmits both HD video and power via the same coaxial cable

Type	Analog
Megapixel	2 MP
Objective	Motionless
Focus	2.8 mm
Lighting	IR
Lighting distance	30 m
Protection	IP67
Material	Plastic



Detailed

Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux withIR
Shutter Time	PAL: 1/25s to 1/50,000 s;NTSC: 1/30s to 1/50,000 s
Day □ Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	

Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length □ FOV	2.8 mm, horizontal FOV:103.55° 3.6 mm, horizontal FOV: 82.63° 6 mm, horizontal FOV: 54.38° 8 mm, horizontal FOV:37.96 12 mm, horizontal FOV:24.36
Lens Mount	M12
Illuminator	
Supplement LightRange	Up to 30 m
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080P@25fps NTSC: 1080P@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR, BLC
Noise Reduction	2D DNR
Supplement Detection(PIR)	
PIR Range	Up to 40 m
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ±30%/PoC.af, max. 4W
Material	Plastic
Dimension	110 mm × 93.2 mm (4.33" × 3.67")
Weight	Approx. 350 g(0.77 lb.)
Operating Condition	-40 °C to 60 °C(-40 °F to 140 °F), humidity 90% or less(non-

	condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67