

## Kamera DS-2CE56D0T-IRP

DS-2CE56D0T-IRP 2,8mm 2mp IR 20m HD TVI TURRET KAMERA HIKVISION

- 2 MP turret camera
- Smart IR: up to 20 m IR distance

Növ	Analoq
Megapixel	2 MP
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	20 m
Material	Plastik



## Ətraflı

<b>Camera</b>	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01Lux @ (F2.0, AGC ON),0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30s to 1/50,000 s
Day □ Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
<b>Lens</b>	
Lens Type	2.8 mm Fixed Lens

Focal Length□ FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 60°, diagonal FOV: 122°
Lens Mount	M12
<b>Image</b>	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, SmartIR
Frame Rate	TVI: 1080P@30fps, 1080P@25fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC, HLC
White Balance	Auto/Manual
AGC	Yes
<b>Interface</b>	
Video Output	1 HD analog output
<b>General</b>	
Material	Plastic
Dimension	Φ 89.9 mm × 70.1mm (Φ 3.54" × 2.76")
Weight	Approx. 130 g (0.29lb.)
Operating Condition	'-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25%
Consumption	Max. 2.2 W
IR Range	Up to 20 m

---

---

[Daytech.Az](http://Daytech.Az)