

DS-2CE17H0T-IT3F

DS-2CE17H0T-IT3F 3.6mm 5mp IR 40m HD TVI Bullet CAMERA HIKVISION

- High quality imaging with 5 MP, 2560 × 1944 resolution
- 2.8 mm fixed focal lens
- Up to 40 m IR distance for bright night imaging
- One port for four signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)

Type	Analog
Megapixel	5 MP
Objective	Motionless
Focus	2.8 mm
Lighting	IR
Lighting distance	40 m
Protection	IP67
Material	Metal



Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Frame Rate	TVI: 5M@20fps, 4M@30fps, 4M@25fps, 1080p@30fps, 1080p@25fps AHD: 5M@20fps, 4M@30fps, 4M@25fps CVI: 4M@30fps, 4M@25fps CVBS: PAL/NTSC
Resolution	2560 (H) × 1944 (V)
Min. illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	3.6 mm fixed lens

Horizontal Fieldof View	3.6 mm, horizontal FOV: 80°, vertical FOV: 63°, diagonal FO V:105° 6 mm, horizontal FOV:57°, vertical FOV: 43°, diagonal FOV:72°
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation 0 to 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Language	English
Functions	Brightness, Sharpness, Mirror,Smart IR
2D DNR	Yes
Interface	
Video Output	TVI/AHD/CVI/CVBS
General	
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 4.3 W
Protection Level	IP67
Material	Front Cover: Metal Main Body: Plastic
IR Range	Up to 40 m

Communication	HIKVISION-C
Dimensions	78.9 mm × 75.4 mm × 216.6mm (3.10" × 2.97" × 8.53")
Weight	Approx. 330 g (0.73lb.)