

DS-2CE10HFT-F28

DS-2CE10HFT-F28 2.8mm 5mp LED 20m ColorVu Bullet HD CAMERA HIKVISION

- 5 MP full time color bullet camera
- 24/7 full color imaging
- 2.8 mm fixed focal lens
- Warm supplementary light with 20 m range
- Clear imaging even against strong back lighting due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- Water and dust resistant (IP67)
- 4 in 1 (4 signals TVI/AHD/CVI/CVBS).
- DS-2CE10HFT-F28 2.8mm 5mp LED 20m ColorVu Bullet HD CAMERA HIKVISION
- 5 MP full time color bullet camera
- 24/7 full color imaging
- 2.8 mm fixed focal lens
- Warm supplementary light with 20 m range
- Clear imaging even against strong back lighting due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- Water and dust resistant (IP67)
- 4 in 1 (4 signals TVI/AHD/CVI/CVBS).

Type	Analog
Megapixel	5 MP
Objective	Motionless
Focus	2.8 mm
Lighting	LED
Lighting distance	20 m
Protection	IP67
Material	Metal



Detailed

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944(V)
	TVI: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080p@30fps, 1080p@25fps CVI: 4MP@30fps, 4MP@25fps

Frame Rate	AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps CVBS: PAL/NTSC
Min. illumination	0.0005 Lux @ (F1.0,AGC ON), 0 Lux with White Light
Shutter Time	PAL: 1/25s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm fixed lens
Horizontal Field of View	2.8 mm, horizontal FOV:99.7°, vertical FOV:72°, diagonal FOV:139.8°
Lens Mount	M16
Day & Night	Color
WDR (Wide DynamicRange)	≥130 dB
Angle Adjustment	Pan: 0 to 360°,Tilt: 0 to 90°, Rotation: 0 to 360°
Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR/BLC/HLC/Global/HLS/Anti-banding
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable motion areas
Noise Reduction	3D DNR
Language	English
Function	Brightness, Sharpness, Mirror, Smart Light
Interface	

Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40°F to 140 °F), humidity 90% or less(non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 3.5W
Protection Level	IP67
Material	Metal
White Light Range	Up to 20 m