

AE-DC4328-K5

AE-DC4328-K5 2ch (buckline) dash kamera

- Front 2K HD camera, support 105°horizontally, 123°diagonal rear camera 1080P HD camera; adjustable up and down, left and right angles 15°.
- Display: 3 inch touch screen, Resolution : 854\*480.
- Built-in G-Sensor sensor, emergency video starts recording when the vehicle is in collision or severe vibration, and emergency video backup is locked.
- Voice recognition: Support 9 voice commands such as “open screen”, “display pre-recording”, “display post-recording”, “view all”, “close screen”, “video lock”, “I want to take a photo”, “open recording”, “close recording” etc.
- Communication: Built-in Wi-Fi module.
- Support Micro SD card for video recording, up to 256GB, loop video, seamless connection without missing seconds
- Support mobile APP connection, real-time viewing of video, video playback and parameter setting
- Easy installation, simple operation, plug and record, automatic recording after power on



Ətraflı

Model	AE-DC4328-K5
Camera	
Image Sensor	Front camera: GC4653 Rear camera: GC2053/BG0836
Angle Adjustment	adjustable up and down, left and right angles 15°
Power-off Memory	Yes
Lens	
Lens Type	G+P
Aperture	F1.55

<b>Wi-Fi</b>	
Frequency Range	2412-2472MHZ
Channel Bandwidth	20MHZ
<b>Interface</b>	
Built-in Microphone	Yes
Built-in Speaker	Yes
<b>General</b>	
GPS	No
WiFi	2.4G
Wi-Fi Support	Yes
Resolution	Front: 1440P@30fps, 1080P@30fps Rear: 1080P@25fps
Max. Resolution	1440P@30fps
Video Compression	H.265
FOV	Front camera 123° (D), 105° (H), 56° (V) Rear camera 125° (D), 110° (H), 62° (V)
Camera Dimension	9mm×55mm×42mm (3.50 x 2.16" x 1.65")"
Camera Weight	110g (0.24 lb)
Software Reset	Yes
Online Upgrade	Yes
Power Consumption and Current	□5W(Rear camera)
Power Supply	5V DC, 2 A
Power Interface	Micro
Working temperature	-20 °C to 70 °C (-4 °F to 158 °F)

Working humidity	95%(Max)
Storage	TF card, 16GB to 128 GB
Display	3 inches (854*480)
OSD	Display time, date, etc
Image format	JPEG
Speech recognition	Yes