

IDS-7208HQHI-M1/S

Video recorder iDS-7208HQHI-M1/S AcuSense DIGITAL VIDEO RECORDER HIKVISION

- 8 channels and 1 HDD 1U AcuSense DVR
- False alarm reduction through human and vehicle target classification based on deep learning
- Efficient H.265 pro+ compression technology
- Encoding ability up to 3K/5M Lite @ 12 fps
- 5 signals input adaptively (HDTV/AV/HD/SD/TV/NTSC/PAL)
- Up to 12 network cameras can be connected.

| | |
|--------------------|-----------|
| Number of channels | 8 channel |
| Type | XVR |
| Megapixel | 6 MP |
| Max HDD count | 1 HDD |
| Max HDD capacity | 10 TB |



Detailed

| | |
|------------------------------|---|
| Motion Detection 2.0 | |
| Human/Vehicle Analysis | <p>Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p> <p>Quick search by object or event type is supported;</p> |
| Perimeter Protection | |
| Human/Vehicle Analysis | Up to 4-ch |
| Facial Detection | |
| Facial Detection and Capture | Face picture detection, face picture search |
| Recording | |

| | |
|------------------------|--|
| Video Compression | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 |
| | |
| Video Bitrate | 32 Kbps to 6Mbps |
| Dual-stream | Support |
| Stream Type | Video, Video& Audio |
| Audio Compression | G.711u |
| Audio Bitrate | 64 Kbps |
| Video and Audio | |
| IP Video Input | 2-ch (up to 10-ch) Up to 6 MP resolution Enhanced IP mode on: 4-ch (up to 12-ch), each up to 4 Mbps Support H.265+/H.265/H.264+/H.264 IP cameras |
| Analog VideoInput | 8-ch;BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection |
| HDMI Output | 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60 Hz, HDMI/VGA simultaneous output |
| CVBS Input | PAL/NTSC |
| CVBS Output | 1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480 |
| Synchronous playback | 8-ch |
| HDTVI Input | 3K(2960 × 1665)@20 fps, 5 MP(2560× 1944)@20 fps, 4 MP(2560× 1440)@30 fps, 4MP(2560 × 1440)@25 fps,1080p@30 fps, 1080p@25 fps,720p@30 fps, 720p@25 fps |
| VGA Output | 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60 Hz |
| AHD Input | 5 MP(2560 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps |

| | |
|----------------------------|--|
| HDCVI Input | 5 MP(2592 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps |
| Audio Output | 1-ch, RCA (Linear, 1 KΩ) |
| Audio Input | 1-ch, RCA (2.0 Vp-p,1 KΩ)□8-ch via coaxialcable |
| Two-Way Audio | 1-ch, RCA (2.0Vp-p, 1 KΩ) (using the first audioinput) |
| Network | |
| Total Bandwidth | 96 Mbps |
| Network Protocol | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS,iSCSI, UPnP™, HTTPS , ONVIF |
| Remote Connection | 64 |
| Network Interface | 1, RJ45 10M/100M self-adaptive Ethernet interface |
| Auxiliary Interface | |
| SATA | 1 SATA interface |
| Capacity | Up to 10 TB capacity for each disk |
| Serial Interface | RS-485 (half-duplex) |
| USB Interface | 2 × USB 2.0 |
| Alarm In/Out | N/A |
| General | |
| Power Supply | 12 VDC |
| Consumption | ≤ 18 W |
| Working Temperature | -10 °C to +55°C (+14 °F to +131°F) |
| Working Humidity | 10% to 90% |
| Dimension (W × D × H) | 315 × 242 × 45 mm (12.4× 9.5 × 1.8 inch) |
| Weight | ≤ 1.78 kg (3.9lb) |

Daytech.Az