

Videoregistrator DS-7116NI-Q1/M

Videoregistrator DS-7116NI-Q1/M NETWORK DIGITAL VIDEO RECORDER HIKVISION

- H.265+/H.265/H.264+/H.264 video compression
- Up to 160 Mbps incoming bandwidth, and 80 Mbps outgoing bandwidth
- Up to 16-ch network camera inputs
- Up to 16-ch 1080p decoding capability
- HDMI and VGA simultaneous output

Kanal sayı	16 kanal
Növ	NVR
Megapiksel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB



Ətraflı

Video and audio	
IP video input	16 channels Resolution up to 4 MP
Input Bandwidth	40 Mbit/s
Output Bandwidth	60 Mbit/s
HDMI output	1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA output	1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Video output	Simultaneous HDMI/VGA output
Decoding	

Decoding Format	H.265+ / H.265 / H.264+ / H.264
Recording permission	4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronized playback	16 channels
Playback options	16 channels, @ 1080p (25 fps), 2 channels @ 4 MP (25 fps)
Stream type	Video, video and audio
Net	
Remote connection	16
Network protocol	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP
Network interface	1, RJ45 auto 10/100M Ethernet
Auxiliary Interfaces	
SATA	1 SATA interface
Capacity	Up to 6 TB each drive
USB	Rear: 2 × USB 2.0
Basics	
Nutrition	DC 12 V, 1.5 A
Power consumption (without HDD)	≤ 10 W
Working temperature	-10 to +55 °C
Operating humidity	From 10 to 90%
Dimensions	265 × 225 × 48 mm (10.4 × 8.9 × 1.9")
Weight (without storage)	≤ 1 kg
Certificates	
FCC	Part 15 Subpart B, ANSI C63.4-2014
C.E.	EN50130-4, EN 61000-3-2, EN 61000-3-3

[Daytech.Az](#)