

DS-D5022FN-C

DS-D5022FN-C MONITOR HIKVISION

- Ultra-thin device body with ultra-thin border for 3 sides.
- 2 channels of 8 bit/10 bit LVDS HD (1920 × 1080) display.
- 178° ultra-wide view screen.
- 3D noise reduction.
- Low blue light design for eye care.
- Dual interface of HDMI and VGA.
- Support VESA wall mount.

Ölçü	22"
Görüntü imkanı	FHD
Tezlik	60 Hz
Panel	İPS

**Ətraflı**

Model	DS-D5022FN-C
Screen Size	21.5"
Active Display Area	478.656 (H) mm × 260.28(V) mm
Resolution	1920 × 1080
Backlight	E-LED
Pixel Pitch	0.0831 (H) mm × 0.241 (V) mm

Brightness	250 cd/□
Viewing Angle	178°/178°
Color Depth	8 bit
Contrast Ratio	3000 : 1
Response Time	6.5 ms□typ□
Refresh Rate	60 Hz
Haze	25 %
Reliability	7 × 16 H
Color Gamut	72%
Video □ Audio Input	HDMI 1.4 × 1, VGA × 1, AudioIn × 1
Power Supply	100-240 VAC,50/60 Hz
Power Consumption	≤ 22 W
Standby Consumption	≤ 0.5 W
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	20% to 90% RH (Non-Condensing)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140°F)
Storage Humidity	10% to 90% RH (Non-Condensing)
Casing Material	Plastic
VESA	75 mm × 75 mm, 4-M6 × 6 screw holes

Bezel Width	1.88 mm (top/left/right), 19 mm (bottom)
Product Dimensions (W × H × D)	With base: 492.356(W) mm × 390.11 (H) mm × 200.20 (D) mm (19.38' × 15.36' × 7.88') Without base:492.356 (W) mm × 289.680 (H) mm × 43.88 (D) mm (19.38' × 11.40' × 1.73')