

HAC-HDW1209TLQP-LED-0280B-S2

DH-HAC-HDW1209TLQP-LED-0280B-S2 2MP HD-CVI 20M Full-color Starlight Eyeball Kamera

- Full-color starlight
- 20 m illumination distance
- Max. 30fps@1080P
- Built-in mic (-A)
- Quick-to-install eyeball saves installation time
- CVI/CVBS/AHD/TVI switchable
- Fixed lens (2.8 mm;3.6 mm optional)
- IP67, 12V±30% DC

Type	Analog
Megapixel	2 MP
Objective	Motionless
Focus	2.8 mm
Lighting	LED
Lighting distance	20 m
Microphone	Mic
Protection	IP67
Material	Plastic



Detailed

Camera	
Image Sensor	1/2.8" CMOS
Effective Pixels	1920(H)×1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s
Minimum Illumination	0.01 Lux/F1.6, 0 Lux white light on
S/N Ratio	More than 65dB

IR Distance	20 m (65.61 ft)
IR On/Off Control	Auto / Manual
IR LEDs	1

Lens

Lens Type	Fixed lens / Fixed iris
Mount Type	M12
Focal Length	2.8 mm
Max Aperture	F1.6
Angle of View	2.8 mm: 126.2° × 106° × 56.5° (diagonal × horizontal × vertical);
Focus Control	N/A
Close Focus Distance	2.8 mm: 0.7 m (2.29 ft)

DORI Distance

Note: The DORI distance is a “general proximity” of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.

	DORI Definition	Distance
Detect	25px/m (8px/ft)	2.8mm: 43.9 m (144.02 ft)
Observe	63px/m (19px/ft)	2.8mm: 17.5 m (57.41 ft)
Recognize	125px/m (38px/ft)	2.8mm: 8.8 m (28.87 ft)
Identify	250ppm (76px/ft)	2.8mm: 4.4 m (14.43 ft)

Pan / Tilt / Rotation

Pan/Tilt/Rotation	<p>Pan: 0° ~ 360°</p> <p>Tilt: 0° ~ 90°</p> <p>Rotation: 0° ~ 360°</p>
Video	
Resolution	1080p (1920 × 1080); 720p (1280× 720); 960H (960 × 576/960 × 480)
Frame Rate	<p>CVI:</p> <p>PAL: 1080p@25 fps; 720p@25 fps;</p> <p>NTSC: 1080p@30 fps; 720p@30 fps;</p> <p>AHD:</p> <p>PAL: 1080p@25 fps;</p> <p>NTSC: 1080p@30 fps</p> <p>TVI:</p> <p>PAL: 1080p@25 fps;</p> <p>NTSC: 1080p@30 fps</p> <p>CVBS:</p> <p>PAL: 960H;</p> <p>NTSC: 960H</p>
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto / Manual
Smart IR	Auto / Manual

Certifications	
Certifications	CE (EN55032, EN55024, EN50130-4)

	FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Electrical	
Power Supply	12V DC \pm 30%
Power Consumption	Max 3.0W (12V DC, IR on)
Environmental	
Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 95% RH * Start up should be done at above -40°C (-40°F)
Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 95% RH
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Inner core: metal + plastic Cover: plastic Pedestal: plastic
Dimensions	ϕ 97.1 mm \times 91.4 mm (ϕ 3.82" \times 3.6")
Net Weight	0.21 Kg (0.46 lb)
Gross Weight	0.28 Kg (0.62 lb)