

HAC-HDW1200TP-Z-A-2712-S6

DH-HAC-HDW1200TP-Z-A-2712S6 2MP 60M IR Göz Altı Kamerası

- 2 megapikselli HDCVI video camera
- Piksellər: 1920 × 1080
- IR=60m
- f=2.7 - 12 mm
- 1080P (1920 × 1080)
- BLC / HLC / DWDR
- IP67

Type	IP
Megapixel	2 MP
Objective	Motorized
Focus	2.7-12 mm
Lighting	IR
Lighting distance	60 m
Microphone	Mic
Protection	IP67
Material	Metal



Model	HAC-HDW1200TP-Z-A-2712-S6
Camera	
The matrix	1 / 2,7" CMOS
Effective pixels	1920 × 1080
Scanning system	Progressive
Electronic shutter speed	PAL:1 / 25s – 1 / 100000s NTSC:1 / 30s – 1 / 100000s

Signal-To-Noise Ratio	>65dB				
Mines. lighting	60 m (196.9 ft)				
IR Control On / Off	Auto / Manual				
IR LEDs	2				
Pan / Tilt / Rotate Range	Pan:0° - 360° Tilt: 0° - 78° Rotation:0° - 360°				
Lens					
Lens Type	Motorized varifocal				
Auto Focus	No				
Focal length	2.7 mm-12 mm				
Max. aperture	F1.7				
Viewing angle	105.9° ~ 33.4°				
IR Type	Fixed				
Closed focal length	1.2 m (3.9 ft)				
DOPE Distance	Lens	Detection	Notification	Speech recognition	Identification
	2.7 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5 m (16.4 ft)
Video					
Frame Rate	CVI:1080P 25 / 30fps; 720P 25 / 30fps; 720P 50 / 60fps; AHD:1080P 25 / 30fps; 720P 25 / 30fps; TVI:1080P 25 / 30fps; 720P 25 / 30fps; 720P 50 / 60fps; CVBS:960H				
Permission	1080P (1920 × 1080); 720P (1280 × 720); 960H (960 × 576 / 960 × 480)				
Day / Night	Automatic switching by ICR				
BLC	BLC / HLC / DWDR				
WDR	DWDR				

White Balance	Auto / Manual
Gain control	Auto / Manual
Noise reduction	2D NR
Smart IR	There are
Prevent fogging	There are
Display	Off / On
Privacy Mask	Off / On (8 Zones, Rectangle)
Certificates	
Certificates	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024: 2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC, Part 15, Subsection B, ANSI C63. 4-2014) UL (UL60950-1+CAN/CSA C22. 2 No. 60950-1)
Port	
Audio output	Single-channel built-in microphone
Video output	CVI / TVI / AHD / CVBS video output options via a single BNC port
Protection	
Degree of protection	IP67
Environment	
Operating temperature	-30 ° C to + 60 ° C (-22 ° F to 140 ° F); <95% (Non-condensing)
Storage temperature	-30 ° C to + 60 ° C (-22 ° F to 140 ° F); <95% (Non-condensing)
Electrical properties	
Power supply	12V ±30% DC
Power consumption	Max.8.2 W (DC12V, IR on)
General information	
Body	Aluminum

Mounting type	φ14
Sizes	Φ122 mm × 104.8 mm (Φ4. 80 "× 4.13")
Net Weight	0.57 kg (1.26 lb)
Gross Weight	0.72 kg (1.59 lb)