

IPC-HFW1239S1P-LED-0360B-S5-QH2

- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition Kamera
- Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate
- Built-in LEDs, max LED distance: 15 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection

Növ	IP
Megapixel	2 MP
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	LED
İşıqlandırma məsafəsi	15 m
Qoruma	IP67
Material	Plastik



Ətraflı

Model	IPC-HFW1239S1P-LED-0360B-S5-QH2
Camera	
The matrix	1/2. 7" 2 MP Progressive Scan CMOS
Effective pixels	1920 × 1080
ROM	16 MB
RAM	64 MB
Scanning system	Progressive
Electronic shutter speed	Auto / Manual 1 / 3 s – 1 / 100000 s
Mines. lighting	0.005 Lux at F1. 6

LED distance	15 m (49.2 ft)				
LED On / Off Control	Auto / Manual				
Light-emitting diodes	1				
Pan / Tilt / Rotate Range	Horizontal:0° - 360° Vertical: 0° - 90° Rotation:0° - 360°				
Lens					
Lens Type	Fixed				
Focal length	3.6 mm				
Max. aperture	F1.6				
Viewing angle	Pan:91° x Tilt: 48° x Diagonal:109°				
IR Type	Fixed				
Closed focal length	1.1 m (3.6 ft)				
DOPE Distance	Lens	Detection	Notification	Speech recognition	Identification
	3.6 mm	53.3 m (179.9 ft)	21.3 m (69.9 ft)	10.7 m (35.1 ft)	5.3m (12.1 ft)
Video					
Video compression	H.265; H.264; H.264H; H.264B; MJPEG				
Smart Codec	There are				
Video Frame Rate	Main stream: 1920 × 1080 (1 fps - 25 / 30 fps) Additional stream: 704 × 576 (1 fps - 25 fps) 704 × 480 (1 fps-30 fps)				
Streaming capabilities	2 streams				
Permission	1080p (1920 × 1080); 1.3 m (1280 × 960);720p (1280 × 720); D1 (704 × 576 / 704 × 480); VGA (640× 480); CIF (352 × 288 / 352 × 240)				
Data transfer	CBR / VBR				

rate monitoring	
Video bitrate	H.264:32 Kbps - 6144 Kbps H.265:12 Kbps - 6400 Kbps
Day / Night	Color / B / W
BLC	There are
HLC	There are
WDR	DWDR
White Balance	Auto / Natural / Street Lamp / Outdoor activities / Manually / Regionally
Gain control	Auto / Manual
Noise reduction	3D DNR
Motion Detection	Off / On (4 Zones, Rectangle)
Area of Interest (RoI)	Yes (4 Zones)
Smart Light	There are
Rotate the frame	0 ° / 90 ° / 180 ° / 270 ° (Support 90 ° / 270 ° with 1080p resolution.)
Display	There are
Privacy Mask	4 Zones
Network	
Network	RJ-45 (10 / 100 Base-T)
Protocol	IPv4; IPV6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; DDNS ;
Compatibility	ONVIF (S Profile); CGI; P2P; Genetec
User / Host	20
Keeping	FTP; Dahua Cloud
Browser	IE Chrome Firefox
Management	Smart PSS; DSS; DMSS

software	
Smartphones	IOS; Android
Certificates	
Certificates	CE-LVD:EN62368-1 CE-EMC:Electromagnetic Compatibility Directive 2014/30 / EU FCC: 47 CFR FCC, Part 15, Subsection B
Protection	
Degree of protection	IP67
Environment	
Operating conditions	-40 ° C to + 60 ° C (-40 ° F to + 140 ° F) / Less than ≤ 95%
Storage temperature	-40 ° C to + 60 ° C (-40 ° F to +140 ° F)
Electrical properties	
Power supply	12V DC / PoE (802.3af)
Power consumption	< 4.8 W
General information	
Body	Metal +Plastic
Colour	White
Mounting type	M12
Sizes	162.6 mm × Φ70 mm (6.4 "× Φ2. 8")
Net Weight	0.22 kg (0.4 lb)
Gross Weight	0.34 kg (0.7 lb)