

IPC-HDBW3249EP-AS-NI-0360B

- 2-megapixel IP video camera designed for installation in internal security systems
- Pixels:1920 × 1080
- F=3.6 mm
- Video compression:H. 265; H. 264; H. 264H; H. 264B; MJPEG
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card
- 12V DC/PoE power supply
- IP67, IK10 protection
- SMD Plus

Növ	IP
Megapixel	2 MP
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	İR
İşıqlandırma məsafəsi	30 m
Qoruma	IP67
Material	Metal



Ətraflı

Model	IPC-HDBW3249EP-AS-NI-0360B
Camera	
The matrix	1/2. 8” 2 MP Progressive Scan CMOS
Effective pixels	1920 × 1080
ROM	128 MB
RAM	512 MB
Scanning system	Auto / Manual 1 / 3 s – 1 / 100,000 s

Signal-To-Noise Ratio	> 56dB				
Mines. lighting	0.0015 Lux F1. 0				
Pan / Tilt / Rotate Range	Pan:0° - 355° Tilt: 0° - 65° Rotation:0°- 355°				
Lens					
Mounting type	M12				
Focal length	3.6 mm				
Max. aperture	F1.0				
Viewing angle	Horizontal:84°; Vertical: 45°; Diagonal:99°				
Aperture Control	Fixed value				
Closed focal length	1.7 m (5.6 ft)				
DOPE Distance	Lens	Detection	Notification	Speech recognition	Identification
	3.6 mm	55.2 m (181.1 ft)	22.1 m (72.5 ft)	11.0 m (36.1 ft)	5.5 m (18.0 ft)
Professional, Intellectual properties					
Perimeter protection	Stretching,Intrusion (Recognizing vehicles and people)				
Smart Search	Work together with Smart NVR to perform accurate intelligent search, event extraction, and integration with video events				
Video					
Video compression	H. 265; H. 264; H. 264H; H. 264B; MJPEG (Supported only by an additional stream)				
Smart Codec	Smart H.264+				
Video Frame Rate	Main stream:(1920 × 1080 1 – 25 / 30 fps) Additional stream:(704 × 576 1 – 25 / 704 × 480 1 - 30 fps) Third stream:(1280 × 720 1 – 25 / 30 fps)				
Streaming capabilities	3 streams				

Permission	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480);CIF (352 × 288/352 × 240)
Managing the bitrate	CBR; VBR
Video bitrate	H.264:3 kbps-8192 kbps H.265:3 kbps-8192 kbps
Day / Night	Color / B / W
BLC	There are
WDR	120 dB
White Balance	Auto / Natural / Street Lamp / Outdoor activities / Manually / Regionally
Gain control	Auto / Manual
Noise reduction	3D DNR
Motion Detection	Off / On (4 Zones, Rectangle)
Area of Interest (RoI)	Yes (4 Zones)
Rotate an image	0° / 90° / 180° / 270° (Support 90 ° / 270 ° with a resolution of 1920 × 1080 and below)
Display	There are
Privacy Mask	4 Zones
Audio	
Audio compression	G.711a; G.711Mu; G726; AAC
Anxiety	
Disturbing events	No SD card; SD card is full; SD card error; Less SD card maintenance time (smart card support); Network outage; IP conflict; Illegal access; Voltage detection; Security exception; Motion detection; Video violation; Scene change; Abnormal input; Intensity change; Stretching; Intrusion; SMD
Network	
Network	RJ-45 (10 / 100 Base-T)
SDK and API	There are
Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Многоадресная рассылка; ICMP; IGMP; NFS; PPPoE; 802.1x; SNMP

Compatibility	ONVIF (Profile S / Profile G); CGI; P2P; Milestone; Genetec
Self-adaptation of the scene	There are
User / Host	20 (Total throughput:64 M)
Keeping	FTP; SFTP; Micro SD card (max 256 GB supported); Dahua Cloud; NAS
Web Browsing	IE: IE8, IE9, IE11 Chrome Firefox
Management software	Smart PSS, DSS, DMSS
Smartphones	IOS; Android
Certificates	
Certificates	CE-LVD:EN62368-1 CE-EMC:Electromagnetic Compatibility Directive 2014/30 / EU FCC:47 CFR FCC Part 15, Subsection B UL / CUL:UL60950-1 CAN / CSA C22.2 No. 60950-1-07
Ports	
Audio Input	1 channel (RCA Port)
Audio Output	1 channel (RCA Port)
Alarm Input	1 channel Input:5mA 3V-5V D
Alarm Output	1 channel Output:300mA 12V DC
Protection	
Degree of protection	IP67; IK10
Environment	
Operating conditions	-40 ° C to + 60 ° C (-40 ° F to +140 ° F) / Less than 95%
Storage conditions	-40 ° C to + 60 ° C (-40 ° F to +140 ° F)
Electrical properties	

Power supply	12V DC / PoE
Power consumption	
General information	
Body	Metal
Mounting type	M12
Colour	White
Sizes	81mm × Φ109. 9mm (3.2 "× Φ4. 3")
Net Weight	378 g (0.8 lb)
Gross Weight	523 g (1.2 lb)