

XVR1B08-I

- H.265+/H.265 dual-stream video compression
- Supports Full channel AI-Coding
- Supports HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth
- Up to 4 channels video stream (analog channel) SMD Plus

Kanal sayı	8 kanal
Növ	XVR
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB



Ətraflı

System	
Main Processor	Embedded processor
Operating System	Embedded linux
SMD Plus	
Performance	4 channels
AI Search	Search by target classification (Human, Vehicle)
Video and Audio	
Analog Camera Input	8 channels, BNC
HDCVI Camera Input	1080p@ 25/30 fps, 720p@25/30 fps
AHD Camera Input	1080p@ 25/30 fps, 720p@ 25/30 fps
TVI Camera Input	1080p@25/30 fps, 720p@25/30 fps
CVBS Camera Input	PAL/NTSC
IP Camera Input	8+2 channels, each channel up to 6MP
Audio In/Out	1/1, RCA
Two-way Talk	Reuse audio in/out, RCA
Recording	
Compression	AI Coding/H.265+/H.265/H.264+/H.264
Resolution	1080N; 720p; 960H; D1; CIF
Record Rate	Main Stream: 8-channel: the 1st channel 1080N/720p(1 fps-25/30 fps), others 1080N/720p(1 fps-15 fps); 960H/D1/CIF/(1 fps-25/30 fps) Sub stream: 8-channel: CIF (1 fps-7 fps)
Bit Rate	32 kbps-4096 kbps per channel
Record Mode	Manual; Schedule (General, Continuous); MD (Video detection: Motion Detection, Video Loss, Tampering); Alarm; Stop

Record Interval	1 min- 60 min (default: 60 min), Pre-record: 1 s-30 s, Post-record: 10 s-300 s
Audio Compression	G.711A; G.711U; PCM
Audio Sample Rate	8 KHz, 16 bit per channel
Audio Bit Rate	64 kbps per channel
Display	
Interface	1 HDMI; 1 VGA
Resolution	1920 × 1080, 1280 × 1024, 1280 × 720
Multi-screen Display	When IP extension mode not enabled: 1/4/8/9
	When IP extension mode enabled: 1/4/8/9/16
OSD	Camera title; Time; Video loss; Camera lock; Motion detection; Recording
Network	
Interface	1 RJ-45 Port (100 Mbps)
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4/IPv6; Wi-Fi; 3G/4G; SNMP; UPnP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; P2P; IP Search (Supports Dahua IP camera, DVR, NVS, etc.)
Max. User Access	128 users
Smart Phone	iPhone; iPad; Android
Interoperability	ONVIF 16.12, CGI Conformant
Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis
Alarm input	N/A
Relay Output	N/A
Playback and Backup	
Playback	1/4/9
Search Mode	Time/Date; Alarm; MD and Exact Search (accurate to second)
Playback Function	Play; Pause; Stop; Rewind; Fast play; Slow Play; Next File; Previous File; Next Camera; Previous Camera; Full Screen; Repeat; Shuffle; Backup Selection; Digital Zoom
Backup Mode	USB Device/Network
Storage	
Internal HDD	1 SATA port, up to 6 TB capacity
eSATA	N/A
Auxiliary Interface	
USB	2 USB ports (USB 2.0)
RS485	N/A
RS232	N/A
Electrical	
Power Supply	DC 12 V/1.5 A
Power Consumption	< 7 W
(Without HDD)	
Construction	
Dimensions	Cooper 1U, 198 mm × 202.9 mm × 41.5 mm
	(7.81' × 7.99' × 1.63')
Net Weight	0.62 kg (1.37 lb)
(without HDD)	
Gross Weight	1.13 kg (2.49 lb)
Installation	Desktop installation
Environmental	
Operating Conditions	-10 °C to +45 °C (+14 °F to +113 °F), 0%-90% (RH)
Storage Conditions	-20 °C to +70 °C (-4 °F to +158 °F), 0%-90% (RH)
Third-party Support	
Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more
Certifications	
Certifications	FCC: Part 15 Subpart B
	CE: CE-LVD: EN 60950-1/IEC 60950-1
	CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN 50130; EN 55024