

XVR1B04H-I

- Comes with an internal 1TB SSD, and can record videos for about 22 days
- H.265+/H.265 dual-stream video compression
- Supports Full-channel AI-Coding
- Supports HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth
- Up to 4 channels video stream (analog channel) SMD Plus

| | |
|--------------|---------|
| Kanal sayı | 4 kanal |
| Növ | XVR |
| Megapiksel | 2 MP |
| Max HDD sayı | 1 HDD |



Ətraflı

| System | |
|----------------------|---|
| Main Processor | Industrial-grade processor |
| Operating System | Embedded Linux |
| Operating Interface | Web; Local GUI |
| SMD Plus | |
| SMD Plus by Recorder | 4-channel: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change |
| Audio and Video | |
| Analog Camera Input | 4 BNC ports, CVI access by default, supports HDCVI/ AHD/TVI/CVBS auto-detect |
| Camera Input | 1. CVI: 5 MP, 4 MP, 1080p@25/30 fps, 720p@50/60 fps, 720p@25/30 fps. 2. TVI: 5 MP, 4 MP, 1080p@25/30 fps, 720p@25/30 fps. 3. AHD: 5 MP, 4 MP, 1080p@25/30 fps, 720p@25/30 fps. 4. CVBS: PAL/NTSC |

| | |
|-----------------------------|---|
| IP Camera Input | Up to 6 channels of IPC access 2 IP channels by default + 4 channels (analog channels are converted to IP channels) incoming bandwidth: 32 Mbps, recording bandwidth: 32 Mbps and outgoing bandwidth: 32 Mbps *After IP channels are added beyond the existing channels, the AI Function (SMD) will be disabled. |
| Encoding Capacity | Main Stream: All channel 5M-N@ (1 fps-10 fps); 4M-N/1080p@ (1 fps-15 fps); 1080N/720p/960H/D1/CIF@ (1 fps-25/30 fps) Sub stream: D1/CIF (1 fps-15 fps) |
| Dual-stream | Yes |
| Video Bit Rate | 32 kbps-6144 kbps |
| Audio Sampling | 8 kHz, 16 bit |
| Audio Bit Rate | 64 kbps |
| Video Output | 1 HDMI, 1 VGA HDMI/VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 |
| Multi-screen Display | When IP extension mode not enabled: 1/4 When IP extension mode enabled: 1/4/6 |
| Third-party Camera Access | ONVIF; Panasonic; Sony; Axis; Arecont; Pelco; Canon; Samsung |
| Compression Standard | |
| Video Compression | AI Coding; Smart H.265+; H.265; Smart H.264+; H.264 |
| Audio Compression | G.711a; G.711u; PCM |
| Network | |
| Network Protocol | HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P |
| Mobile Phone Access | iOS; Android |
| Interoperability | ONVIF 21.06; CGI Conformant |
| Browser | Chrome IE9 or later Firefox |
| Network Mode | Single-address mode |
| Recording Playback | |
| Record Mode | General, motion detection, alarm,POS |
| Recording Playback | 1/4 |

| | |
|-----------------------|--|
| Backup Method | USB device and network |
| Playback Mode | Instant playback, general playback, event playback, tag playback |
| Alarm | |
| General Alarm | Motion detection, video loss, tampering |
| Anomaly Alarm | No disk, disk error, low space, offline, ip conflict, MAC conflict |
| Alarm Linkage | Record, snapshot (panoramic), IPC external alarm output, access controller, voice prompt, buzzer, log, preset, email |
| Ports | |
| Audio Input | 1-channel RCA 4-channel BNC (Coaxial Audio) |
| Audio Output | 1-channel RCA |
| Two-way Talk | Yes (share the same audio input with the first channel) |
| HDD Interface | 1 SSD: 1 TB (replaceable with 256 GB or 512 GB) Stores for 22 days under default settings. |
| USB | 2 USB ports (USB 2.0) |
| HDMI | 1 |
| VGA | 1 |
| Network Port | 1 (10/100 Mbps Ethernet port, RJ-45) |
| General | |
| Power Supply | 12 VDC, 1.5 A |
| Power Consumption | <6 W (with SSD) |
| Net Weight | 0.55 kg (1.21 lb) |
| Gross Weight | 1.02 kg (2.25 lb) |
| Product Dimensions | 197.0mm × 203.4 mm × 41.5 mm (7.76' × 8.01' × 1.63') (W × D × H) |
| Packaging Dimensions | 332.0 mm × 240.0 mm × 64.0 mm (13.07" × 9.45" × 2.52") (W × D × H) |
| Operating Temperature | -10 °C to +55 °C (+14 °F to +131 °F) |
| Operating Humidity | 0%–90% (RH) |
| Installation | Desktop |
| | |

| | |
|----------------|---|
| Certifications | FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024 |
|----------------|---|

Daytech.Az