

## XVR5232AN-I3

### Video recorder XVR5232AN-I3

32-channel SMD Plus for analog channels or 40-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles.

4-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI.

2-channel face recognition for analog channels which supports face comparison.

16-channel AI Coding saves on storage and bandwidth while maintaining the details of targets in videos.

Supports HDCVI, AHD, TVI, CVBS and IP video input.

Supports up to 40-channel IP camera input and each channel can be up to 6 MP. The incoming bandwidth reaches 160 Mbps.

Smart H.265+ and H.265 dual-stream video compression.

IoT and POS capabilities.

Number of channels	32 channel
Type	XVR
Megapixel	6 MP
Max HDD count	2 HDD
Max HDD capacity	16 TB



## Detailed

System	
Main Processor	Industrial-grade processor
Operating System	Embedded Linux
Operating Interface	Web; Local GUI
Perimeter Protection	

Perimeter Performance AI by Recorder (Number of Channels)	Advanced Mode: 2 channels, 10 IVS rules for each channel General Mode: 4 channels, 10 IVS rules for each channel
<b>Face Detection</b>	
Face Attributes	6 attributes
Face Detection Performance of AI by Recorder (Number of Channels)	2 channels (up to 12 face images/s each channel)
Face Recognition	
Face Database Capacity	Up to 10 face databases with 10,000 images.
Face Recognition Performance of AI by Recorder (Number of Channels)	2 channels
<b>SMD Plus</b>	
SMD Plus by Recorder	32 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
SMD Plus by Camera	40 channels
AI Video Quality Analytics	
AI Video Quality Analytics by Recorder	32 channels: Supports detecting brightness levels, color cast, defocus, overexposure, contrast levels, black and white
<b>Scene Changing</b>	
Scene Changing by Recorder	1 channel
Irregular Black Block Masking	
Irregular Black Block Masking by Recorder	1 channel

<b>Audio and Video</b>	
Analog Camera Input	32 BNC ports, supports HDCVI/AHD/TVI/CVBS auto-detect
Camera Input	<p>1. CVI: 5 MP@25 fps; 5 MP@20 fps; 5 MP@10/12.5 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@50/60 fps; 720p@25/30fps.</p> <p>2. TVI: 5 MP@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps.</p> <p>3. AHD: 5 MP@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps.</p>
IP Camera Input	<p>Up to 40 channels of IPC access</p> <p>8 IP channels by default +32 channels (analog channels are converted to IP channels)</p> <p>incoming bandwidth: 160 Mbps, recording bandwidth: 160 Mbps and outgoing bandwidth: 160 Mbps</p> <p>*After IP extension is enabled, Video Quality Analytics, Scene Changing, Face Recognition, Face Detection, SMD, Perimeter Protection cannot be used.</p>
Encoding Capacity	<p>Main stream:</p> <p>5 MP Mode: 4-ch 5 MP@(1 fps-6 fps); others 5M-N@(1 fps-12 fps)</p> <p>5M-N Mode: 5M-N@(1 fps -12 fps); 4M-N/1080p@(1 fps-15 fps); 1080N/720p/960H/D1/CIF@(1 fps-25/30 fps)</p> <p>Sub stream: D1/CIF@(1 fps-15 fps)</p>
Dual-stream	Yes
Video Bit Rate	32 kbps-6144 kbps
Audio Sampling	8 kHz, 16 bit
Audio Bit Rate	64 kbps
Video Output	<p>1 HDMI, 1 VGA, 1 TV</p> <p>HDMI : 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720</p> <p>VGA: 1920 × 1080, 1280 × 1024, 1280 × 720</p> <p>*Simultaneous/heterogeneous video sources output for VGA and HDMI is</p>

	configurable.
Multi-screen Display	1/4/8/9/16/25/36
Third-party Camera Access	Panasonic; Sony; Hanwha; Axis; Arecont; ONVIF
<b>Compression Standard</b>	
Video Compression	AI Coding; Smart H.265+; H.265; Smart H.264+; H.264
Audio Compression	G.711a; G.711u; PCM
<b>Network</b>	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.)
Mobile Phone Access	iOS; Android
Interoperability	ONVIF 23.12 (Profile T; Profile S; Profile G); CGI; SDK
Browser	Chrome; IE; Safari; Edge; Firefox
<b>Recording Playback</b>	
Record Mode	General; alarm; motion detection; intelligent; POS
Recording Playback	1/4/9/16
Backup Method	USB device and network
Playback Mode	Instant playback; general playback; event playback; tag playback; smart playback

Storage	
Disk Group	Yes
<b>Alarm</b>	
General Alarm	Motion detection; alarm box; HDCVI alarm; camera external alarm; network alarm; PIR alarm
Anomaly Alarm	Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
Intelligent Alarm	Face detection; face recognition; perimeter protection; SMD Plus
Alarm Linkage	Record; snapshot (panoramic); IPC external alarm output; audio; buzzer; log; preset; email
<b>Ports</b>	
TV Output	1 channel
Audio Input	1-channel RCA 32-channel BNC (Coaxial Audio)
Audio Output	1-channel RCA
Two-way Talk	Yes (share the same audio input with the first channel)
Disk Interface	2 SATA ports. Each disk can contain up to 16 TB. This limit varies depending on the environment temperature.
RS-485	1
USB	

	2 (1 front USB 2.0 port, 1 rear USB 3.0 port)
HDMI	1
VGA	1
Network Port	1 (10/100/1000 Mbps Ethernet port, RJ-45)
General	
Power Supply	12 VDC, 5 A
Power Consumption	
Net Weight	1.98 kg (4.36 lb)
Gross Weight	3.15 kg (6.94 lb)
Product Dimensions	375.0 mm × 289.6 mm × 53.0 mm(14.76" × 11.40" × 2.09") (W × D × H)
Packaging Dimensions	433.0 mm × 141.0 mm × 366.0 mm(17.05" × 5.55" × 14.41") (W × D × H)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operating Humidity	10%-90% (RH), non-condensing
Installation	Desktop

Certifications

CE: CE-LVD: EN 60950-1/IEC 60950-1

CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024

FCC: Part 15 Subpart B

---

[Daytech.Az](http://Daytech.Az)