

Access Control ASI1201A

- Touch keyboard and LCD display
- Support multiple cards(default IC card) (“-D” means ID EM card)
- Support card, password and combination
- TCP/IP to PC · Wiegand or RS-485 interface to reader
- Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- Anti-passback, multi-card open
- Software attendance
- Support 128 efficient time and holiday schedules
- Watch dog function ensure device free from halting



Ətraflı

Model	ASI1201A
Basic information	
Main Processor	32 bits
Memory	16M
RTC	There are

Voice prompt	No
Beep sound	Buzzer
Keyboard	Sensitive touch keyboard with blue backlit
Input / Output ports	
Entrance	1 Door sensor ,1 Exit button, 2 Alarm
Exit	3 Output relays (Door lock, bell, alarm)
Reader	1 reader
Card reading	
Reading format	13.56 MHz
Reading range	3-8 cm (max.)
Response time	
Container	
Cardholders	30,000
Events	150,000
Functions	
Managing users	General, VIP, Guest, Patrol, Blacklist
Alarm function	Door lock alarm after waiting time
Setting up a period	Supports 128 schedule groups, 128
Interface	
To the PC	RJ45(10 / 100M)
To the reader	Wiegand / RS485
Environment	
Operating temperature	-5°C ~ +55°C
Operating humidity	≤95%
Electrical properties	

Power supply	9-15DC / 200mA
<b>General information</b>	
Sizes	97mm x 16mm x 150mm
Weight	0.3 kg

---