

Access Control ASI1201A

Touch keyboard and LCD display
Support multiple cards (default IC card) (" -D" means ID EM card)
Support card, password and combination
TCP/IP to PC · Wiegand or RS-485 interface to reader
Door time out alarm, intrusion alarm, duress alarm and tamper alarm
Anti-passback, multi-card open
Software attendance
Support 128 efficient time and holiday schedules
Watch dog function ensures device free from halting



Detailed

Model	ASI1201A
Basic information	
Main Processor	32 bits
Memory	16M
RTC	There are

Voice prompt	No
Beep sound	Buzzer
Keyboard	Sensitive touch keyboard with blue
Input / Output ports	
Entrance	1 Door sensor ,1 Exit button, 2 Alar
Exit	3 Output relays (Door lock, bell, ala
Reader	1 reader
Card reading	
Reading format	13.56 MHz
Reading range	3-8 cm (max.)
Response time	
Container	
Cardholders	30,000
Events	150,000
Functions	
Managing users	General, VIP, Guest, Patrol, Blacklis
Alarm function	Door lock alarm after waiting time
Setting up a period	Supports 128 schedule groups, 128
Interface	
To the PC	RJ45(10 / 100M)
To the reader	Wiegand / RS485
Environment	
Operating temperature	-5°C ~ +55°C
Operating humidity	≤95%
Electrical properties	

Power supply	9-15DC / 200mA
General information	
Sizes	97mm x 16mm x 150mm
Weight	0.3 kg

Daytech.Az