

Access Control ASI1212D

Support multiple cards (default IC card) (" -D" means ID EM card)
 Support card, password, fingerprint and combination
 TCP/IP to PC, support WAN communication
 Support P2P add device
 Wiegand or RS-485 interface to reader
 Door time out alarm, intrusion alarm, duress alarm and tamper alarm
 Anti-passback, multi-card open
 Support 128 efficient time and holiday schedules
 USB import/export configuration or log file



Detailed

Model	ASI1212D
Basic information	
Main Processor	32 Bits
Flash memory	32M
RTC	There are
Voice prompts	There are
Beep sound	Buzzer

Login Ports / Exit point	
Entrance	1 door sensor, 1 exit button, 1 alarm input
Exit	Relay: 1 Door Lock TTL: 1 Ring, Alarm x 1
Card Reader	
Reading format	13.56 MHz (Mifare)
Reading range	3-8 cm (max.)
Response time	
Fingerprint reading	
Response time	≤0.5 s
Speech recognition time	≤ 1.5 s
FAR	≤0.00004 %
FRR	≤0.15 %
Container	
Cardholders	30,000
Events	150,000
Fingerprints	3000
Functions	
Network	P2P, DHCP
Access control	Anti-passback, Multi-door lock, multi-card unlock
Managing users	General, VIP, Guest, Patrol, Blacklist, Forced
Alarm function	Door lock alarm after waiting time has expired, security alarm, alarm system, burglar alarm
Setting up a period	Supports 128 groups for schedules, 128 groups for periods, and 128 groups for weekends
Interface	

To the PC	RJ45 (10 / 100M)
To the reader	Wiegand 34 / 26, RS485
Protection	
Degree of protection	IP65
Environment	
Operating temperature	-5°C - +55°C
Operating humidity	≤95%
Electrical properties	
Power supply	9 - 15DC / 200mA
General information	
Sizes	205 mm x 33 mm x 83 mm
Weight	0.44 kg