

Camera UAC-T132-F28

Camera UAC-T132-F28 Uniview 2MP

- High quality imaging with 2MP resolution
- TVI/AHD/CVI/CVBS
- 3D noise reduction technology delivers clean and sharp images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- OSD configuration menu in 11 languages

Type	Analog
Megapixel	2 MP
Objective	Motionless
Focus	2.8 mm
Lighting	IR
Lighting distance	20 m
Protection	IP67
Material	Plastic



Model	UAC-T132-F28	UAC-T132-F40
Sensor		
Pixel	2MP	
Size	1/3.2"	
Minimum illumination	0.02 lux (F2.0, AGC ON) 0 lux (IR ON)	
Lens		
Lens	2.8mm	4.0mm

Lens mount	M12	
Angle of view	H: 99.7° V: 55.1° D: 117.1°	H: 87.7° V: 47.6° D: 106.9°
Illuminator		
Illuminator	One IR illuminator	
Illumination distance	20m	
Lifetime	≥60,000 hours	
Video		
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)	
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC	
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s	
Image		
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR	
Day/Night	Three modes: Auto (default), Day, Night	
Digital noise reduction	2D/3D	
White balance	Two modes: Auto (default), Manual	
WDR	DWDR	
Smart IR	Support	
Flip	Supports 180° horizontal flip, 180° vertical flip	
Defog	N/A	
Audio		
Microphone	N/A	
Camera audio	N/A	
Interface		

Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
Operating environment	
Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge protection	4kV
Ingress protection	N/A
General	
Power	DC 12V (±25%), with reverse polarity protection, Max 1.9W
Dimensions	Φ85mm*72mm (diameter*height)
Material	Plastic
Weight	89.3g (0.20lb)
Certification	
EMC	CE-EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)